



**Unmatched  
safety and  
reliability**



**Quick and  
Easy  
Installation**



**Reliable  
Freeze  
Protection**



**Various  
Lengths  
Available**



# Ready. Set. Heat.

Introducing ReadyTrace™, your go-to solution for safeguarding commercial buildings from freezing temperatures. Made in the USA with superior materials, it offers unmatched safety and reliability at an unbeatable value.





Length (ft)	Min Watts 10C (50F)	On Pipe Max Watts			
		10C (50F)	0C (32F)	-20C (-4F)	-40C (-40F)
6	36	67	75	92	107
12	72	134	150	184	214
18	108	200	226	276	322
24	144	267	301	367	429
36	216	401	451	551	643
50	300	557	626	766	893
75	450	835	940	1148	1340
100	750	1114	1253	1531	1786

On Roof Max Watts			
10C (50F)	0C (32F)	-20C (-4F)	-40C (-40F)
87	98	119	139
174	195	239	279
261	293	358	418
347	391	478	557
521	586	717	836
724	814	995	1161
1086	1221	1493	1742
1448	1629	1991	2322

Length (ft)	Min Amps 10C (50F)	On Pipe Max Amps			
		10C (50F)	0C (32F)	-20C (-4F)	-40C (-40F)
6	0.3	0.6	0.6	0.8	0.9
12	0.6	1.1	1.3	1.5	1.8
18	0.9	1.7	1.9	2.3	2.7
24	1.2	2.2	2.5	3.1	3.6
36	1.8	3.3	3.8	4.6	5.4
50	2.5	4.6	5.2	6.4	7.4
75	3.8	7.0	7.8	9.6	11.2
100	6.3	9.3	10.4	12.8	14.9

On Roof Max Amps			
10C (50F)	0C (32F)	-20C (-4F)	-40C (-40F)
0.7	0.8	1.0	1.2
1.4	1.6	2.0	2.3
2.2	2.4	3.0	3.5
2.9	3.3	4.0	4.6
4.3	4.9	6.0	7.0
6.0	6.8	8.3	9.7
9.0	10.2	12.4	14.5
12.1	13.6	16.6	19.4

## ReadyTrace™ is as easy as:

Ensure all installation and use comply with the user manual, local electrical codes, and regulations. Secure the heat trace according to the guidelines to ensure even heat distribution and avoid physical damage.



1. Uncoil




2. Plug in



3. Heat

## Need help?



Scan for videos, instructions, and more.



# Sécurité et fiabilité inégalées



**Installation  
rapide et  
facile**



**Protection  
fiable contre  
le gel**



**Longueurs  
variées  
offertes**



## Prêt. Installez. Chauffez.

Voici ReadyTrace™, votre solution de référence pour protéger les bâtiments commerciaux contre les températures glaciales. Fabriqué aux États-Unis avec des matériaux de qualité supérieure, il offre une sécurité et une fiabilité inégalées à un prix imbattable.



Longueur (pi)	Watts min 10C (50F)	Sur le tuyau Watts max				Sur le toit Watts max			
		10C (50F)	0C (32F)	-20C (-4F)	-40C (-40F)	10C (50F)	0C (32F)	-20C (-4F)	-40C (-40F)
6	36	67	75	92	107	87	98	119	139
12	72	134	150	184	214	174	195	239	279
18	108	200	226	276	322	261	293	358	418
24	144	267	301	367	429	347	391	478	557
36	216	401	451	551	643	521	586	717	836
50	300	557	626	766	893	724	814	995	1161
75	450	835	940	1148	1340	1086	1221	1493	1742
100	750	1114	1253	1531	1786	1448	1629	1991	2322

Longueur (pi)	Ampères min 10C (50F)	Sur le tuyau Ampères max				Sur le toit Ampères max			
		10C (50F)	0C (32F)	-20C (-4F)	-40C (-40F)	10C (50F)	0C (32F)	-20C (-4F)	-40C (-40F)
6	0.3	0.6	0.6	0.8	0.9	0.7	0.8	1.0	1.2
12	0.6	1.1	1.3	1.5	1.8	1.4	1.6	2.0	2.3
18	0.9	1.7	1.9	2.3	2.7	2.2	2.4	3.0	3.5
24	1.2	2.2	2.5	3.1	3.6	2.9	3.3	4.0	4.6
36	1.8	3.3	3.8	4.6	5.4	4.3	4.9	6.0	7.0
50	2.5	4.6	5.2	6.4	7.4	6.0	6.8	8.3	9.7
75	3.8	7.0	7.8	9.6	11.2	9.0	10.2	12.4	14.5
100	6.3	9.3	10.4	12.8	14.9	12.1	13.6	16.6	19.4

## ReadyTrace™ c'est aussi simple que:

ÉAssurez-vous que l'installation et l'utilisation respectent le manuel d'utilisateur, les codes électriques locaux et la réglementation en vigueur. Fixez le câble chauffant conformément aux directives afin de garantir une répartition uniforme de la chaleur et d'éviter tout dommage physique.



**1. Déroulez**




**2. Branchez**



**3. Chauffez**

## Besoin d'aide?



Scannez pour visionner des vidéos, des instructions et plus encore.